



|   |                |   |
|---|----------------|---|
| <b>Anziehvorschrift für Zylinderkopf</b>                | <b>548.906</b> | <br>Das Original |
| <b>Tightening Instructions for Cylinder Head</b>        |                |   |
| <b>Instructions de serrage pour culasse</b>             |                |   |
| <b>Prescripciones de apriete para culatas</b>           |                |   |
| passend für / suitable for<br>adaptable à / adaptable a |                | <b>Mercedes-Benz</b>  |

Schraubenkopf / Head shape      Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete  
Tête de vis / Cabeza de tornillo



372.940  
M 12x1,75x205



|   |                         |             |
|---|-------------------------|-------------|
| Anziehen/<br>Tightening/<br>Serrage/<br>Apriete | * M12<br>10 Nm<br>60 Nm | M8<br>20 Nm |
|   | ➤ 90°<br>➤ 90°<br>➤ 90° |             |

Zeichenerklärung / Explanations / Explication / Explicacion

|   |   |                              |                                |                                       |
|---|---|------------------------------|--------------------------------|---------------------------------------|
| * | neue Zylinderkopfschrauben verwenden        | use new cylinder head bolts  | utiliser des vis neuves        | emplar tornillos nuevos               |
| ★ | Warmlauf (80°C)                             | warm up time (80°C)          | chauffage (80°C)               | calentamiento (80°C)                  |
| □ | Schrauben einzeln lösen und wieder anziehen | loosen and tighten each bolt | deserrer et serrer vis par vis | aflojar y apretar tornillo a tornillo |
| ● | Setzzeit                                    | relaxation time              | durée de tassement             | tiempo de espera                      |
| ➤ | Drehwinkel                                  | torque angle                 | angle de serrage               | ángulo de giro                        |

**Motortyp / Engine type / Type de moteur / Tipo de motor**

Ø 84,1 / 1,2 mm links/left/gauche/izquierda/sin

Mot: OM 642.852, 858  
300/350 CDI/BlueTEC

C218, W212, S212, X218

ElringKlinger AG, Max-Eyth-Str.2  
72581 Dettingen / Erms. Tel. 07123/724 601

**\*548.906\***